



00100A8H400XXX

Cable Assembly

SMA(F)R/A-客製剝線 for $\Phi 1.13\text{mm}$ Cable Assembly

Features

- ✓ High Repeatability
- ✓ Low VSWR



Electrical Specifications

Impedance	50Ohm
Connection 1	SMA Female Right Angle
Connection 2	Open & Tinned

Material


Part	Material	Plated
1.SMA Connector		
Body	Brass	Gold
Center Pin	Phosphor Bronze	Gold
Insulator	Teflon	
2.Heat Shrink Tube		Black
3.Cable		
$\Phi 1.13\text{mm}$ Mini Coaxial Cable		Gray

Mechanical

Durability	500 Cycles
------------	------------

Outling Drawing (Unit:mm)

DIMENSIONS	TOLERANCES
0.5~10mm	± 0.2
11~100mm	± 5.0
101~500mm	± 10.0
501~1000mm	± 15.0
1001~2000mm	± 20.0
2000~5000mm	± 50.0






Wake up your further dream.



φ 1.13mm Mini Coaxial Cable Physical Characteristics

Center Conductor	Construction Size	0.08±0.003mm
	Standard Diameter	0.24mm Silver Coated Copper
Insulation	Average Thickness	0.22mm
	Diameter	0.68±0.02mm FEP
Braid Shield	Construction	16/4/0.050 ±0.003 mm
	Coverage	90%
	Diameter	0.9±0.02mm Tinned-Coated Copper
Jacket	Average Thickness	0.13mm
	Overall Diameter	1.13±0.05mm FEP(Gray)
Min. Bending Radius		6.8mm

φ 1.13mm Mini Coaxial Cable Electrical Characteristics

Impedance	50 ± 3ohms	
Operating Temperature	-60~+200°C	
Capacitance	96±3pF/m	
Conductor Resistance	545 ohms/KM at 20°C (max.)	
Operating Frequency	6GHz	
Velocity of propagation	69%	
 Jacket Braid Shield Conductor Insulation	Maximum Attenuation(dB/M) @ 2GHz	2.8
	2.4GHz	3.1
	3GHz	3.5
	4GHz	4.0
	5GHz	4.6
	6GHz	5.1

整條 Assembly 之 Loss 為以下 3 項數值之加總

1. 接頭 Loss : 0.06 x √ 頻率 (2 端都有接頭則需將此數值 x2) (I-PEX ,Murata Connector 不適用此公式)
2. 組裝 Loss : 0.12 (2 端都有組裝則需將此數值 x2)
3. 線材 Loss : 依上述 Maximum Attenuation 換算需求長度之 Loss