




00800N1G04H-XX

Attenuator

6GHz N 20W Fixed Attenuator

Features

- ✓ Small Size
- ✓ Low VSWR



Electrical Specifications

Frequency	DC-6GHz
Standard Values	3,5,6,10,20,30,40dB
Attenuation Accuracy	3,5,6,10 dB: $\pm 0.4\text{dB}(\text{Max.})@DC-4\text{GHz}$, $\pm 0.5\text{dB}(\text{Max.})@4-6\text{GHz}$ 20dB : $\pm 0.5\text{dB}(\text{Max.})@DC-4\text{GHz}$, $\pm 0.6\text{dB}(\text{Max.})@4-6\text{GHz}$ 30dB : $\pm 0.6\text{dB}(\text{Max.})@DC-4\text{GHz}$, $\pm 0.8\text{dB}(\text{Max.})@4-6\text{GHz}$ 40dB : $\pm 0.7\text{dB}(\text{Max.})@DC-4\text{GHz}$, $\pm 0.8\text{dB}(\text{Max.})@4-6\text{GHz}$
VSWR	1.20:1(Max.)@DC-4GHz, 1.25:1(Max.)@4-6GHz
Average Power	20W@25°C
Peak Power	4KW(5μsec pulse, 0.25% duty cycle)
Impedance	50Ohm
Connection 1	N Male
Connection 2	N Female

Mechanical

Durability	500 Cycles
------------	------------


Environmental

Operating Temperature	-55°C~125°C
-----------------------	-------------

Material

Part	Material	Plated
Connection	Brass	Tri-Metal

Outling Drawing (Unit:mm)



Test Report

