




0120A02056002D

Power Divider

0.5–6GHz 2Way SMA Fwd.35W/Rev.2W Isolated Power Divider

Features

- ✓ Use as Divider or Combiner
- ✓ Low Insertion Loss & VSWR
- ✓ High Isolation



Test Report

Electrical Specifications

Frequency	0.5-6GHz
Insertion Loss (Above Theoretical Loss:3.0dB)	0.8dB(Max.)
VSWR(Input)	1.8:1(Max.)@0.5-0.7GHz 1.3:1(Max.)@0.7-6GHz
VSWR(Output)	1.5:1(Max.)@0.5-0.7GHz 1.3:1(Max.)@0.7-6GHz
Isolation	12dB(Min.)@0.5-0.7GHz 19dB(Min.)@0.7-6GHz
Phase Unbalance	±2°(Max.)
Amplitude Unbalance	±0.3dB(Max.)
Flatness	0.3dB@0.7-1GHz 0.3dB@1.7-2.2GHz 0.3dB@2.4-2.5GHz 0.5dB@4.9-5.8GHz
Power:Forward:	35W (Avg.) 100W(Peak)
Reverse:	2W(Avg.) 20W(Peak)
Impedance	50Ohm
Connection	SMA Female

Mechanical

Durability	500 Cycles
------------	------------


Environmental

Operating Temperature	-55°C~85°C
-----------------------	------------


Material

Part	Material	Plated
Connector	Brass	Tri-Metal


Outling Drawing (Unit:mm)




Insertion Loss/VSWR




Isolation



Amplitude Unbalance



Phase Unbalance



All Specification Changed Without Notification.