



0120F02082402Y

Power Divider

**10-2350MHz 2Way F Type 0.5W
Isolated Power Divider**

Features

- ✓ Use as Divider or Combine
- ✓ High Isolation



Electrical Specifications

Frequency	10-2,350MHz
Insertion Loss (Above Theoretical Loss:3.0dB)	4.3dB(Max.)@10-40MHz 4.8dB(Max.)@40-806MHz 6.0dB(Max.)@950-1,450MHz 7.0dB(Max.)@1,450-2,150MHz 7.5dB(Max.)@2,150-2,350MHz
Return Loss(Input)	12dB(Min.)@10-806MHz&950-1,450MHz 8dB(Min.)@1,450-2,350MHz
Return Loss(Output)	10dB(Min.)@10-40MHz 12dB(Min.)@40-806MHz&950-1,450MHz 10dB(Min.)@1,450-2,350MHz
Isolation	15dB(Min.)@10-40MHz 20dB(Min.)@40-200MHz 23dB(Min.)@200-806MHz 22dB(Min.)@950-2,150MHz 20dB(Min.)@2,150-2,350MHz
Power:	0.5W (Avg.)
Impedance	75Ohm
Connection	F Female(F 母頭可接受公針外徑:1.0mm~1.6mm, 但若1.6mm外徑公針太頻繁使用易導致母pin彈性疲乏)