



0120F04082401Y

Power Divider

10-2350MHz 4Way F Type 0.5W
Isolated Power Divider

Features

- ✓ Use as Divider or Combine
- ✓ High Isolation



Electrical Specifications

Frequency	10-2,350MHz
Insertion Loss (Above Theoretical Loss:6.0dB)	7.8dB(Max.)@10-40MHz 8.5dB(Max.)@40-806MHz 9.5dB(Max.)@950-1,450MHz 12dB(Max.)@1450-2,150MHz 13dB(Max.)@2,150-2,350MHz
Return Loss(Input)	8dB(Min.)@10-806MHz 10dB(Min.)@950-2,150MHz 8dB(Min.)@2,150-2,350MHz
Return Loss(Output)	8dB(Min.)@10-40MHz 10dB(Min.)@40-806&950-2,150MHz 8dB(Min.)@2,150-2,350MHz
Isolation	22dB(Min.)@10-40MHz 25dB(Min.)@40-806MHz 22dB(Min.)@950-1,450MHz 20dB(Min.)@1,450-2,350MHz
Power:	0.5W (Avg.)
Impedance	75Ohm
Connection	F Female(F 母頭可接受公針外徑:1.0mm~1.6mm, 但若1.6mm外徑公針太頻繁使用易導致母pin彈性疲乏)

All Specification Changed Without Notification.