



0169A00180005W

RF Switch Box

18GHz SMA SP8T Multiple Port RF Switch Box

Features

- ✓ High Repeatability
- ✓ Low VSWR



Electrical Specifications

Frequency	18GHz
VSWR	1.2:1(Max.)@DC-4GHz
	1.3:1(Max.)@4-8GHz
	1.4:1(Max.)@8-12.4GHz
	1.6:1(Max.)@12.4-18GHz
Insertion Loss	0.2dB(Max.)@DC-4GHz
	0.3dB(Max.)@4-8GHz
	0.4dB(Max.)@8-12.4GHz
	0.6dB(Max.)@12.4-18GHz
Isolation(Ports)	75dB(Min.)@DC-4GHz
	65dB(Min.)@4-8GHz
	60dB(Min.)@8-18GHz
DC Power	12V/2A(24W)
RF Power	50W
Impedance	50Ohm
Operating Life	1,000,000 Cycles (Min.)
Switching Time	15ms
Coaxial Connection	SMA Female(1 input/8 out)
Control Interface:	LAN
Operating Voltage	DC12V/290mA

Environmental

Operating Temperature	-25~65℃
-----------------------	---------

支援程式化語言 c++, c#, Java, Delphi, VB, PHP, Python等, 有支援Socket連線及傳送指令功能的程式都可以適用。

Outling Drawing (Unit:mm)

