



SOLVANG TECHNOLOGY INC.

www.solvangtech.com

Email : sales@solvangtech.com

6GHZ N MALE TO 4.3/10 MALE 89 SERIES

CABLE ASSEMBLY LOW PIM:<-160DBC

P/NO.STI03-8902-XX



SPECIFICATION

Frequency	DC-6GHz
Impedance:	50Ohm
VSWR:	1.25:1(Max.)
PIM:	<-160dBc(1800MHz@2x43dBm)
Durability:	500 Cycles
Connection 1:	N Male
Connection 2:	4.3/10 Male
RF Cable:	89 Series Flexible Coaxial Cable
Cable Overall Diameter:	7.0mm

MATERIAL LIST


Part	Material	Plated
Connector Body	Brass	White Bronze
Moulded	PVC/PE	Black



TESTING DATA (100% S-PARAMETER TESTED)

183cm

Tone Frequency:1805MHz,1880MHz



Any more request, please contact sales@solvangtech.com. Thank you ~



SOLVANG TECHNOLOGY INC.

www.solvangtech.com

Email : sales@solvangtech.com

FLEXIBLE 89 SERIES CABLE



SPECIFICATION

Cut-Off Frequency	19GHz
Impedance:	50Ohm
Capacitance:	95pF/m
Velocity of Propagation:	70%
Shielding Effectiveness:	100dB
Min. Bend Radius Static:	30mm
Repeated Bend Radius:	120mm
Operating Temperature:	-55~125℃

MATERIAL LIST

Part	Material	Diameter
Inner Conductor	Silver Plated Copper	1.63mm
Dielectric	PTFE	5.27mm
Outer Conductor	Tin Soaked Copper Braid	6.20mm
Jacket	FEP	7.0mm

ATTENTION

MHz	dB/m
500	0.17
1000	0.25
3000	0.46
5000	0.63
10000	0.98

POWER

MHZ	Watts CW
500	1600
1000	1341
3000	745
5000	433
10000	288

Any more request, please contact sales@solvangtech.com. Thank you ~